



The **AP-P1UV** visible and UV visible light spectrophotometer is easy to operate and covers a wide wavelength range. The **AP-P1UV** is accurate and reliable for the most demanding laboratory environments and will offers stable readings every time. Its vivid touch-screen display is visible from any angle, and simple to use, allowing the user to quickly familiarize themselves with the unit.



AVANPRO is the registered trademark of **AVAPRO, Corp**. Avanpro follows a policy of continuous innovation. Product designs and specifications are subject to change without notice.



TECHNICAL DATA

Detector	
Silicon Photodiode	
Range	
Accuracy	
Accuracy	
Scan Speed - Range -0.301-3A, 0-200%T, 0-9999.9C	
Scan Speed - Range -0.301-3A, 0-200%T, 0-9999.9C	
Scan Speed - Range -0.301-3A, 0-200%T, 0-9999.9C	
Scan Speed - Range -0.301-3A, 0-200%T, 0-9999.9C	
Range	
Stability ≤0.002A/hr. (500nm, 2 hours after preheating) Stray Light ≤0.2%T Baseline - Memory 236KB (Built-in), Unlimited (USB memory stick) Display 5 inches color screen (480 x 272mm) Keypad Touch screen Printer Serial printer, USB (in line with HP PCL3 GUI printing language) Port Serial port (printing), USB-A (storage and printing), USB-B (online and an accordance of the post of	
Stability ≤0.002A/hr. (500nm, 2 hours after preheating) Stray Light ≤0.2%T Baseline - Memory 236KB (Built-in), Unlimited (USB memory stick) Display 5 inches color screen (480 x 272mm) Keypad Touch screen Printer Serial printer, USB (in line with HP PCL3 GUI printing language) Port Serial port (printing), USB-A (storage and printing), USB-B (online and an additional and additional and an additional analysis and additional	
Stability ≤0.002A/hr. (500nm, 2 hours after preheating) Stray Light ≤0.2%T Baseline - Memory 236KB (Built-in), Unlimited (USB memory stick) Display 5 inches color screen (480 x 272mm) Keypad Touch screen Printer Serial printer, USB (in line with HP PCL3 GUI printing language) Port Serial port (printing), USB-A (storage and printing), USB-B (online and an additional and additional and an additional analysis and additional	
Stray Light Baseline Memory 236KB (Built-in), Unlimited (USB memory stick) Display 5 inches color screen (480 x 272mm) Keypad Touch screen Printer Serial printer, USB (in line with HP PCL3 GUI printing language) Serial port (printing), USB-A (storage and printing), USB-B (online and and antimate and antima	
Baseline - 236KB (Built-in), Unlimited (USB memory stick)	
Display Sinches color screen (480 x 272mm)	
Simplay Sinches color screen (480 x 272mm)	
Touch screen	
Printer Serial printer, USB (in line with HP PCL3 GUI printing language) Serial port (printing), USB-A (storage and printing), USB-B (online of the printing) of the printing language) Serial port (printing), USB-A (storage and printing), USB-B (online of the printing), USB-A (storage and printing), USB-B (online of the printing), USB-B (online o	
Serial port (printing), USB-A (storage and printing), USB-B (online) Standard	
Standard 10mm 4-cell holder 10-50mm 4-cell holder,10-100mm 4-cell holder, 10mm-8-cell Automatic Holder, 10-100mm 5-cell Automatic Holder. Micro Cell Holder, Peltier/Si System, Reflectance Accessories, Solid Sample Holder, Water-Jac or 4-cell holder, Test Tube Holder. Photometric Quantitation Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple Holder) 6 languages)
Optional 10-50mm 4-cell holder, 10-100mm 4-cell holder, 10mm-8-cell Automatic Holder, 10-100mm 5-cell Automatic Holder. Micro Cell Holder, Peltier/Si System, Reflectance Accessories, Solid Sample Holder, Water-Jac or 4-cell holder, Test Tube Holder. Photometric Quantitation Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple Holder, 10mm-8-cell Automatic Holder, 10mm-8-cell Automatic Holder, 10mm-8-cell Automatic Holder, 10mm-8-cell Automatic Holder, Micro Cell Holder, Peltier/Si System, Reflectance Accessories, Solid Sample Holder, Water-Jac or 4-cell holder, Test Tube Holder. • Optional 6 languages (English, German, French, Spanish, Portuguese, simple Holder, 10mm-8-cell Automatic Holder, 10mm-8-cell Automatic Holder, 10mm-8-cell Automatic Holder, 10mm-8-cell Automatic Holder, Micro Cell Holder, Peltier/Si System, Reflectance Accessories, Solid Sample Holder, Water-Jac or 4-cell holder, Test Tube Holder.	ne)
Automatic Holder, 10-100mm 5-cell Automatic Holder. Micro Cell Holder, Peltier/Si System, Reflectance Accessories, Solid Sample Holder, Water-Jac or 4-cell holder, Test Tube Holder. Photometric Quantitation Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple Holder, Water-Jac or 4-cell holder, Test Tube Holder. • Quantitation • Spectrum File Management • Glanguages (English, German, French, Spanish, Portuguese, simple Holder, Water-Jac or 4-cell holder, Test Tube Holder. • Glanguages • Glanguages • Glanguages • Glanguages • Glanguages	
Photometric Quantitation Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple Holder, Water-Sadior 4-cell holder, Test Tube Holder.	
Photometric Quantitation Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple Holder, Water-Sadior 4-cell holder, Test Tube Holder. • Quantitation • Spectrum File Management • Of languages (English, German, French, Spanish, Portuguese, simple Holder, Water-Sadior 4-cell holder, Test Tube Holder. • Of Holder, Test Tube Holder. • Of languages (English, German, French, Spanish, Portuguese, simple Holder, Water-Sadior 4-cell holder.	
Photometric Quantitation Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple of the control of the cont	acked 1
Quantitation Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple of the control of the c	
Spectrum File Management System Management Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple of the control of the	
Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple of the control of t	
Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple of the control of t	
Performance Verification 6 languages (English, German, French, Spanish, Portuguese, simple standards)	
6 languages (English, German, French, Spanish, Portuguese, simple Language	
Language	I:C: I
Chinese)	притиеа
Power Supply 100-240V AC, 50/60Hz, 120w	
Dimensions 456 x 360 x 185mm / 18" x 14.2" x 7.3" (w x d x h)	
Weight 10.7kg / 24lb	